



Interface Options

Optional Electrical Interfaces

Available for Models

P100, P117, P119, J205, P605, J705, W117



T

Standard solder type terminals also accept AMP 60789-2 and 60598-4 Pin Receptacles.



TS

Three flat bar terminals with #6-32 pan head screws at right angle



TB

3 standard terminals accept arc-less (or equal) female quick connect terminals



DN

DIN Male Plug "F" Set Only Except "C", "K" & "F" Set on P605 Series Units

For L and U Electrical Interfaces

2 or 3 wire pigtail furnished in 12" length
Standard-supplied #20 AWG Insulated with polyvinyl chloride – 300 volts.

COLOR CODE:

Black – Common
White – N.O.
Red – N.C.



DN Pin-out:
1 = Common
2 = N/C
3 = N/O
Other Pin-outs on request

"M" Interface Quick-Disconnect 3-Pin Connector

This interface is rated as environmentally resisting. It is intended for use where the connector will be subjected to heavy condensation and rapid changes in environmental temperature or pressure. This connector is equivalent to MS3102E-10SL-3P. Applicable to models shown below only.



"M" Interface

P117, J705, J205, P605
"F" Set Only Except "C"
"K" and "F" Set on P605



MS3106E

Connectors – All Models
With "M" Interface

Interface Options

Optional Electrical Interfaces
Available for Model P88



TB

1/4" (TB)
Blade terminals
UL Recognized
CSA Listed



TS

Screw Terminal
UL Listed
(except 25 amp)
CSA Listed

